



ABELROD

DESCRIPTION

An exceptionally strong and lightweight closed cell polyethylene foam rod expansion joint and space filler.

USES

- Ideal as a vertical and horizontal joint filler in concrete, masonry substrates between precast concrete panels, interior walls, sealing skylights, shop fronts and curtain wall construction.
- Can also be used in areas such as swimming pools, in draft proofing, dust sealing, sealing electrical control boxes, truck and trailer construction and as piping around chairs.

FEATURES AND BENEFITS

- Excellent recovery properties enable Abelrod to withstand many years of compression and expansion, ensuring a tight seal from dirt and water entry.
- Highly resistant to weathering and most common chemicals.
- Meets the requirements of Australian Standard AS2170, "Plastic Materials for Food Contact Use".
- Ideal filler prior to application of most sealants.

PREPARATION

- Ensure surface is dry, clean and free from dust, dirt, grease, oil, wax and any other loose contaminating materials.

APPLICATION

- For a good seal, Abelrod should be compressed 30% when in position, i.e. diameter of rod should be at least 30% larger than the width of the expansion joint or gap.

PACKAGING

Available in diameters of 6mm to 50mm in a variety of lengths.

SHELF LIFE

When stored in dry conditions this product has an unlimited shelf life.

TECHNICAL DATA

Properties:	
Appearance:	White Flexible Strips
Solubility in Water:	Insoluble
Density:	30kg/m ³

DISCLAIMER

The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. All workmanship must be carried out in accordance with AS 3958.1 - 1991.

The information contained herein is to the best of our knowledge true and accurate. No warranty is implied or given as to its completeness or accuracy in describing the performance or suitability of the product for a particular application. Users are asked to check that the literature in their possession is the latest issue.

PAREXDAVCO

ParexDavco (Australia) Pty Limited

ABN 28 093 876 558

67 Elizabeth Street Wetherill Park NSW 2164 Australia

Telephone: 61 2 9616 3000 Facsimile: 61 2 9725 5551

Toll Free Technical Advice Line: 1800 653 347

Email: technical@parexdavco.com.au Website: www.parexdavco.com.au

