

# DAVCO DAMPFLEX PRIMER

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 30-Jul-2010  
C9317EC

CHEMWATCH 25964  
Version No:4  
CD 2010/2 Page 1 of 8

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NAME

DAVCO DAMPFLEX PRIMER

### PROPER SHIPPING NAME

PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

### PRODUCT USE

Primer used to enhance the bonding of Dampflex. It is applied to the substrate just prior to the application of Dampflex using a brush, roller or spray.

### SUPPLIER


Company: ParexDavco  
Address:  
67 Elizabeth Street  
Wetherill Park  
NSW, 2164  
Australia  
Telephone: +61 2 9616 3000  
Emergency Tel: 1800 039 008  
Fax: +61 2 9725 5551  
Email: marketing@davco.com.au  
Website: www.davco.com.au

## Section 2 - HAZARDS IDENTIFICATION

### STATEMENT OF HAZARDOUS NATURE

**HAZARDOUS SUBSTANCE. DANGEROUS GOODS.** According to NOHSC Criteria, and ADG Code.

### CHEMWATCH HAZARD RATINGS



### POISONS SCHEDULE

S5

### RISK

Risk Codes

R10  
R20/21  
R36/37/38  
R51/53

Risk Phrases

- Flammable.
- Harmful by inhalation and in contact with skin.
- Irritating to eyes respiratory system and skin.
- Toxic to aquatic organisms may cause long-term adverse effects in the aquatic environment.
- HARMFUL- May cause lung damage if swallowed.
- Vapours may cause drowsiness and dizziness.

R65

R67

### SAFETY

Safety Codes

S36  
S401

Safety Phrases

- Wear suitable protective clothing.
- To clean the floor and all objects contaminated by this material use water and detergent.
- This material and its container must be disposed of in a safe way.
- Keep away from food drink and animal feeding stuffs.
- If swallowed IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).
- Use appropriate container to avoid environmental contamination.
- Avoid release to the environment. Refer to special instructions/Safety data sheets.
- This material and its container must be disposed of as hazardous waste.

S35

S13

S46

S57

S61

S60

continued...

# DAVCO DAMPFLEX PRIMER

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 30-Jul-2010  
C9317EC

CHEMWATCH 25964  
Version No:4  
CD 2010/2 Page 2 of 8  
Section 2 - HAZARDS IDENTIFICATION

---

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

---

NAME	CAS RN	%
naphtha petroleum, light aromatic solvent	64742-95-6.	30-60
xylene	1330-20-7	10-30
other non- hazardous ingredients		NotSpec

---

## Section 4 - FIRST AID MEASURES

---

### SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Avoid giving milk or oils.
- Avoid giving alcohol.
- If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

### EYE

- If this product comes in contact with the eyes:
  - Wash out immediately with fresh running water.
  - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
  - Seek medical attention without delay; if pain persists or recurs seek medical attention.
  - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

- If skin contact occurs:
  - Immediately remove all contaminated clothing, including footwear.
  - Flush skin and hair with running water (and soap if available).
  - Seek medical attention in event of irritation.

### INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
  - Lay patient down. Keep warm and rested.
  - Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
  - Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

### NOTES TO PHYSICIAN

- Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. For acute or short term repeated exposures to xylene:
  - Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.
  - Pulmonary absorption is rapid with about 60-65% retained at rest.
  - Primary threat to life from ingestion and/or inhalation, is respiratory failure.
  - Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> < 50 mm Hg or pCO<sub>2</sub> > 50 mm Hg) should be intubated.

---

## Section 5 - FIRE FIGHTING MEASURES

---

### EXTINGUISHING MEDIA

- - Water spray or fog.
- Alcohol stable foam.
- Dry chemical powder.
- Carbon dioxide.

### FIRE FIGHTING

- - Alert Fire Brigade and tell them location and nature of hazard.
  - May be violently or explosively reactive.
  - Wear breathing apparatus plus protective gloves.
  - Prevent, by any means available, spillage from entering drains or water course.
- When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 500 metres in all directions.

### FIRE/EXPLOSION HAZARD

- - Liquid and vapour are flammable.
  - Moderate fire hazard when exposed to heat or flame.
  - Vapour forms an explosive mixture with air.
  - Moderate explosion hazard when exposed to heat or flame.
- Combustion products include: carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>), other pyrolysis products typical of burning organic material.

continued...

# DAVCO DAMPFLEX PRIMER

Chemwatch Independent Material Safety Data Sheet

Issue Date: 30-Jul-2010

C9317EC

CHEMWATCH 25964

Version No:4

CD 2010/2 Page 3 of 8

Section 5 - FIRE FIGHTING MEASURES

Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.  
May emit clouds of acrid smoke.

## FIRE INCOMPATIBILITY

- - Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

## HAZCHEM

•3Y

## PERSONAL PROTECTION

Glasses:  
Chemical goggles.

Gloves:  
PVC chemical resistant type.

Respirator:  
Type A Filter of sufficient capacity

## Section 6 - ACCIDENTAL RELEASE MEASURES

### MINOR SPILLS

- - Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.

### MAJOR SPILLS

- - Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

## Section 7 - HANDLING AND STORAGE

### PROCEDURE FOR HANDLING

- - Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- DO NOT allow clothing wet with material to stay in contact with skin.
- Electrostatic discharge may be generated during pumping - this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/sec until fill pipe submerged to twice its diameter, then  $\leq 7$  m/sec).
- Avoid splash filling.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of overexposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

Contains low boiling substance:

Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.

- Check for bulging containers.
- Vent periodically
- Always release caps or seals slowly to ensure slow dissipation of vapours.

### SUITABLE CONTAINER

- - Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C).

### STORAGE INCOMPATIBILITY

- - Avoid reaction with oxidising agents.

### PACKAGING MATERIAL INCOMPATIBILITIES

Chemical Name	Container Type
Gasoline (high- aromatic)	" ABS plastic" , Aluminum, EPDM, " Natural rubber" , NORYLr, Silicone

### STORAGE REQUIREMENTS

- - Store in original containers in approved flammable liquid storage area.
- Store away from incompatible materials in a cool, dry, well-ventilated area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.

continued...

# DAVCO DAMPFLEX PRIMER

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 30-Jul-2010  
C9317EC

CHEMWATCH 25964  
Version No:4  
CD 2010/2 Page 4 of 8

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

Source	Material	TWA mg/m <sup>3</sup>	Notes
Australia Exposure Standards	Davco Dampflex Primer (Petrol (gasoline))	900	(see Chapter 16)
Australia Exposure Standards	naphtha petroleum, light aromatic solvent (Petrol (gasoline))	900	(see Chapter 16)

### PERSONAL PROTECTION

#### RESPIRATOR

Type A Filter of sufficient capacity

#### EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

#### HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
  - Wear safety footwear or safety gumboots, eg. Rubber.
- Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:
- frequency and duration of contact,
  - chemical resistance of glove material,
  - glove thickness and
  - dexterity.

#### OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets), non sparking safety footwear.

### ENGINEERING CONTROLS

- For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.
- Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank (in still air).	Air Speed: 0.25- 0.5 m/s (50- 100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min.)

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

Green flammable liquid with a characteristic solvent odour; not miscible with water.

### PHYSICAL PROPERTIES

Liquid.  
Does not mix with water.  
Floats on water.

continued...

# DAVCO DAMPFLEX PRIMER

Chemwatch Independent Material Safety Data Sheet

Issue Date: 30-Jul-2010

C9317EC

CHEMWATCH 25964

Version No:4

CD 2010/2 Page 5 of 8

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	30 (estimated)	Solubility in water (g/L)	Immiscible
Flash Point (°C)	27	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	11.0 (estimated)	Specific Gravity (water=1)	0.87
Lower Explosive Limit (%)	0.8 (estimated)	Relative Vapour Density (air=1)	>1
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available
xylene			
• log Kow (Prager 1995):		3.12- 3.20	

## Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

### CONDITIONS CONTRIBUTING TO INSTABILITY

- - Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

## Section 11 - TOXICOLOGICAL INFORMATION

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

- HARMFUL- May cause lung damage if swallowed.
- Harmful by inhalation and in contact with skin.
- Irritating to eyes, respiratory system and skin.
- Vapours may cause dizziness or suffocation.
- Vapours may cause drowsiness and dizziness.

#### CHRONIC HEALTH EFFECTS

- Not applicable.

### TOXICITY AND IRRITATION

#### XYLENE:

##### NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT:

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

• Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound.

for petroleum:

This product contains benzene which is known to cause acute myeloid leukaemia and n-hexane which has been shown to metabolize to compounds which are neuropathic.

This product contains toluene.

This product contains ethyl benzene and naphthalene from which there is evidence of tumours in rodents

Carcinogenicity: Inhalation exposure to mice causes liver tumours, which are not considered relevant to humans.

##### NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT:

#### TOXICITY

Oral (rat) LD50: >5000 mg/kg \*

Inhalation (rat) LC50: >3670 ppm/8 h \*

• for petroleum:

This product contains benzene which is known to cause acute myeloid leukaemia and n-hexane which has been shown to metabolize to compounds which are neuropathic.

This product contains toluene.

This product contains ethyl benzene and naphthalene from which there is evidence of tumours in rodents

Carcinogenicity: Inhalation exposure to mice causes liver tumours, which are not considered relevant to humans.

Inhalation (rat) TCLo: 1320 ppm/6h/90D-I

\* [Devoe]

#### XYLENE:

#### TOXICITY

Oral (human) LDLo: 50 mg/kg

Oral (rat) LD50: 4300 mg/kg

Inhalation (human) TCLo: 200 ppm

Inhalation (man) LCLo: 10000 ppm/6h

Inhalation (rat) LC50: 5000 ppm/4h

Oral (Human) LD: 50 mg/kg

Inhalation (Human) TCLo: 200 ppm/4h

Intraperitoneal (Rat) LD50: 2459 mg/kg

#### IRRITATION

Nil Reported

#### IRRITATION

Skin (rabbit):500 mg/24h Moderate

Eye (human): 200 ppm Irritant

Eye (rabbit): 87 mg Mild

Eye (rabbit): 5 mg/24h SEVERE

continued...

# DAVCO DAMPFLEX PRIMER

Chemwatch Independent Material Safety Data Sheet

Issue Date: 30-Jul-2010

C9317EC

CHEMWATCH 25964

Version No:4

CD 2010/2 Page 6 of 8

## Section 11 - TOXICOLOGICAL INFORMATION

Subcutaneous (Rat) LD50: 1700 mg/kg

Oral (Mouse) LD50: 2119 mg/kg

Intraperitoneal (Mouse) LD50: 1548 mg/kg

Intravenous (Rabbit) LD: 129 mg/kg

Inhalation (Guinea pig): LC 450 ppm/4h

• The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

Reproductive effector in rats

### CARCINOGEN

Gasoline (NB: Overall evaluation upgraded from 3 to 2B with supporting evidence from other relevant data)	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	2B
---	---	-------	----

Xylenes	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3
---------	---	-------	---

### REPROTOXIN

xylene	ILO Chemicals in the electronics industry that have toxic effects on reproduction	Reduced fertility or sterility
--------	---	--------------------------------

## Section 12 - ECOLOGICAL INFORMATION

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This material and its container must be disposed of as hazardous waste.

Avoid release to the environment.

Refer to special instructions/ safety data sheets.

### Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
xylene	LOW	LOW	LOW	

### GESAMP/EHS COMPOSITE LIST - GESAMP Hazard Profiles

Name / Cas No / RTECS No	EHS	TRN	A1a	A1b	A1	A2	B1	B2	C1	C2	C3	D1	D2	D3	E1	E2	E3
E2- / 1	227	199	(4)	(3)	(3)	(R)	(3)	(1)	1	0	(2)	2	2	TCM		FE	3

Legend:  
 EHS=EHS Number (EHS=GESAMP Working Group on the Evaluation of the Hazards of Harmful Substances Carried by Ships) NRT=Net Register Tonnage, A1a=Bioaccumulation log Pow, A1b=Bioaccumulation BCF, A1=Bioaccumulation, A2=Biodegradation, B1=Acuteaquatic toxicity LC/EC1C50 (mg/l), B2=Chronic aquatic toxicity NOEC (mg/l), C1=Acute mammalian oral toxicity LD50 (mg/kg), C2=Acute mammalian dermal toxicity LD50 (mg/kg), C3=Acute mammalian inhalation toxicity LC50 (mg/kg), D1=Skin irritation & corrosion, D2=Eye irritation & corrosion, D3=Long-term health effects, E1=Tainting, E2=Physical effects on wildlife & benthic habitats, E3=Interference with coastal amenities,  
 For column A2: R=Readily biodegradable, NR=Not readily biodegradable.  
 For column D3: C=Carcinogen, M=Mutagenic, R=Reprotoxic, S=Sensitising, A=Aspiration hazard, T=Target organ systemic toxicity, L=Lung injury, N=Neurotoxic, I=Immunotoxic.  
 For column E1: NT=Not tainting (tested), T=Tainting test positive.  
 For column E2: Fp=Persistent floater, F=Floater, S=Sinking substances.  
 The numerical scales start from 0 (no hazard), while higher numbers reflect increasing hazard.  
 (GESAMP/EHS Composite List of Hazard Profiles - Hazard evaluation of substances transported by ships)

## Section 13 - DISPOSAL CONSIDERATIONS

- Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.
- Otherwise:
- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same

continued...

# DAVCO DAMPFLEX PRIMER

Chemwatch Independent Material Safety Data Sheet

Issue Date: 30-Jul-2010

C9317EC

CHEMWATCH 25964

Version No:4

CD 2010/2 Page 7 of 8

Section 13 - DISPOSAL CONSIDERATIONS

product, then puncture containers, to prevent re-use, and bury at an authorised landfill.

- Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction.
- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

## Section 14 - TRANSPORTATION INFORMATION

Labels Required: FLAMMABLE LIQUID

### HAZCHEM:

•3Y (ADG7)

### ADG7:

Class or division:	3	Subsidiary risk:	None
UN No.:	1263	UN packing group:	III
Special provisions:	163; 223	Packing Instructions:	None
Limited quantities:	5 L	Portable tanks and bulk containers - Instructions:	T2
Portable tanks and bulk containers - Special provisions:	TP1; TP29	Packagings and IBCs - Packing instruction:	P001; IBC03; LP01
Packagings and IBCs - Special packing provisions:	PP1		

Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)  
PAINT RELATED MATERIAL

### Land Transport UNDG:

Class or division:	3	Subsidiary risk:	None
UN No.:	1263	UN packing group:	III

Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)  
PAINT RELATED MATERIAL

### Air Transport IATA:

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1263	Packing Group:	III
Special provisions:	A3		
Cargo Only			
Packing Instructions:	310	Maximum Qty/Pack:	220 L
Passenger and Cargo			
Packing Instructions:	309	Maximum Qty/Pack:	60 L
Passenger and Cargo			
Limited Quantity			
Packing Instructions:	Y309	Maximum Qty/Pack:	10 L

Shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

### Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1263	Packing Group:	III
EMS Number:	F- E , S- E	Special provisions:	163 223 955
Limited Quantities:	5 L		

Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

GESAMP hazard profiles for this material can be found in section 12 of the MSDS.

continued...

# DAVCO DAMPFLEX PRIMER

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 30-Jul-2010  
C9317EC

CHEMWATCH 25964  
Version No:4  
CD 2010/2 Page 8 of 8

---

## Section 15 - REGULATORY INFORMATION

---

### POISONS SCHEDULE

S5

### REGULATIONS

Regulations for ingredients

**naphtha petroleum, light aromatic solvent (CAS: 64742-95-6) is found on the following regulatory lists;**

"Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

**xylene (CAS: 1330-20-7) is found on the following regulatory lists;**

"Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

**No data for Davco Dampflex Primer (CW: 25964)**

---

## Section 16 - OTHER INFORMATION

---

• Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:  
[www.chemwatch.net/references](http://www.chemwatch.net/references).

• The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 30-Jul-2010  
Print Date: 30-Jul-2010

*This is the end of the MSDS.*