



Davco Construction Materials Pty Limited

ABN 28 093 876 558

67 Elizabeth Street Wetherill Park NSW Australia 2164

Telephone: 61 2 9616 3000 Facsimile: 61 2 9725 5551

MATERIAL SAFETY DATA SHEET

1. Identification of Material and Supplier

Product Name	Grey One Pot		
Other Names	Liquid 55		
Recommended Use	Ceramic tile adhesive. Supplied ready for use. Applied with a notched trowel.		
Supplier Name	Davco Construction Materials Pty Ltd		
Address	67 Elizabeth St, Wetherill Park, NSW, Australia 2164		
Web Address	www.davco.com.au		
Telephone	61 2 9616 3000	Facsimile	61 2 9725 5551
Technical Support	1800 653 347	Emergency: Spill, First Aid etc	1800 807 001

2. Hazards Identification

Hazard Classification	This product is non-hazardous according to the criteria of the NOHSC in the form sold. Not a Dg Substance according to the ADG Code. Not a Scheduled Poison according to the SUSDP, Not a flammable or combustible liquid according to AS 1940. All components are listed on the AICS.
Risk Phrases	None allocated (See also page 2)
Safety Phrases	None allocated (See also page 3)

3. Composition/Information on Ingredients

Chemical Identity	Proportion	CAS No
Calcium Carbonate	30 - 60 %	1317-65-3
Rubber Dusts	< 10 %	n.d.
Ingredients which have been determined to be non-hazardous or below cut off values	to 100 %	n.a..

4. First Aid Measures

4.1 Symptoms of Exposure by Route

SWALLOWED

Minor amounts ingested incidental to normal handling will have little or no effect. Larger amounts deliberately ingested will cause nausea, vomiting and stomach discomfort.

EYE

Will cause moderate eye irritation and must be promptly removed by flushing.

SKIN

May cause minor irritation. Should be promptly removed by washing with soap and water.

INHALED

Vapour may cause slight to moderate irritation to upper respiratory tract.

4.2 First Aid Instructions

SWALLOWED

Do not induce vomiting. Rinse mouth clear with water and give two glasses of water to drink. If patient involuntarily vomits encourage to lean forward to avoid aspirating. If symptoms persist seek prompt medical help.

EYE

Immediately: Hold eye open and flush with clean water for at least 15 minutes. While flushing, gently pull upper and lower eyelids away from eyes and ensure carefully flushed. If symptoms persist seek prompt medical attention.

SKIN

Remove contaminated clothing and footwear (while under safety shower if appropriate). Flush affected area with water for 3-5 minutes followed by washing gently with soap and water for a further 5 minutes. Rinse well and pat dry. If symptoms persist seek prompt medical attention.

INHALED

Remove patient (while wearing SCBA if concentrations are high) to fresh air. Allow to rest. Rinse mouth and nose with water. Provide artificial respiration if breathing stops. Seek prompt medical attention unless recovery is virtually immediate.

FIRST AID FACILITIES

Provide normal industrial first aid facilities including eye-wash stations and safety showers as appropriate.

Notes to Physician (for symptoms of over-exposure to this product see above)

Possible symptoms of Chronic Health Effects

Prolonged or repeated skin exposure may cause drying and cracking of the skin.

Possible aggravated pre-existing conditions

None reported

Suggested treatment for acute symptoms, known antidotes

Provide supportive care and treatment based on the patient's reaction to the exposure. For further information contact the :

POISONS INFORMATION CENTRE 13 11 26 in all States (New Zealand Dial 0800 764 766)

5. Fire Fighting Measures

5.1 Flammability and Explosion Hazards

Containers may rupture in fire conditions due to steam pressure. Product is non-flammable as sold but may burn when water content has boiled off.

5.2 Hazardous Combustion Products

CO_x, NO_x and trace amounts of other toxic fumes including polycyclic aromatic vapours if large stocks of product are subjected to heating above 150°C. These vapours have been associated with skin cancers after repeated or prolonged exposures.

5.3 Suitable Extinguishing Media

Select to suit surrounding fires or use water as fine spray or fog.

Hazchem Code: Not allocated

5.4 Precautions for Fire Fighters and Special Equipment

Wear SCBA and full turn out clothing. Avoid bodily contact with substance or run-off. Personnel exposed to smoke in large fires involving large amounts of this product must wash all exposed skin areas immediately on completion of tasks.

6. Accidental Release Measures

6.1 Emergency Procedures – Spills and Leaks (See Section 13 for disposal considerations)

Prevent material entering drains or waterways. Send unnecessary personnel out of area. Wear full protective clothing (including rubber boots and respirator for large industrial storage spills). Spread sand, soil or other inert absorbent over the spill. When saturated collect into metal or plastic drums or pails. Fit lids, label and place containers in a safe area to await disposal.

7. Handling and Storage

7.1 Handling Advice

Wear suitable protective clothing.

7.2 Storage Advice

Store in a cool, dry and well-ventilated area. Keep containers closed when not in use. Requirements under the ADG Code do not apply to this product.

8. Exposure Controls/ Personal Protection

8.1 Exposure Standards

No exposure standards have been set by the NOHSC for this product. Exposure Standards are available for one of the ingredients, however, this is not available as inhalable dusts unless dried product is sawn or sanded.

<i>Substance</i>	<i>TWA</i>	<i>STEL</i>
Calcium Carbonate	10 mg/m ³	n.est.

8.2 Engineering Control Methods

If used out doors natural ventilation is normally adequate. If used in enclosed spaces with poor ventilation provide mechanical ventilation to comfort levels.

8.3 Personal Protective Equipment Respiratory Protection

Not usually required. If vapour concentration is uncomfortably high (unlikely) use respirator fitted with an organic vapour filter to AS 1715 & 1716. Use SCBA in confined spaces. If sanding dried product use painters dust mask.

Eye Protection

Not normally required. If mists or splashes are likely wear safety goggles or full face shield to AS 1337.

Gloves

When applying wear rubber, PVA or neoprene gloves to AS 2161.

Clothing

Wear cotton or Tyvec coveralls fastened at the neck and wrist. Supplement with a rubber or PVA apron if required.

9. Physical and Chemical Properties

Appearance:	Grey paste	Odour:	Slight characteristic
Freezing/ Melting Point:	n.d.	Boiling Point:	Initial 100 °C
Density:	1.45	Vapour Pressure:	n.d.
Solubility in water :	insoluble	Volatiles:	n.d.
Flash Point:	n.a..	Flammability Limits:	n.a..
Auto Ignition Point:	n.a.	AS 1940 Classification:	n.a.
Other Properties	An aqueous solution containing less than 0.2% acticides. Calcium carbonate is present in the paste but is not available as dusts unless dried product is sawn or sanded.		

10. Stability and Reactivity

Under normal conditions of use and handling the product is stable.

11. Toxicological Information

No product relevant data found.

12. Ecological Considerations

May have an adverse effect of aquatic organisms. Does not biodegrade completely.

13. Disposal Considerations

Disposal must be in accordance with local regulations for the disposal of non-hazardous industrial wastes.

14. Transport Information

Requirements under the ADG Code, the IMDG Code or the IATA DG Regulations do not apply to this product.

15. Regulatory Information

No special labelling requirements under the Code of Practice for the labelling of Workplace Substances (NOHSC:2012[1994]), the ADG Code or the SUSDP apply to this product.

16. Other Information

Date of Issue: 8/08/2006 New MSDS (Version 1.0) to comply with National Code of Practice for the Preparation of Material Safety Data Sheets 2nd Edition NOHSC: 2011 (2003).

Data Sources used: in the preparation of this MSDS include: "Chempendium" and "MSDS plus Cheminfo" published in CD format by CCOHS Canada 2005 - 4."TOMES" a CD database published by Micromedex, USA, "Hazardous Properties of Industrial Materials" Van Nostrand Rheinhold NY, USA . "List of Designated Hazardous Substances" NOHSC 10005:1999, "National Exposure Standards" NOHSC 1003:1995 . **Abbreviations used:** n.d = not determined, n.a = not applicable, n.all =not allocated, SUSDP = Standard for the Uniform Scheduling of Drugs and Poisons, ADG = Australian Dangerous Goods Code, IATA = International Air Transport Association, (Dangerous Goods Regulations), IMDG = International Maritime Dangerous Goods (Code)

Disclaimer

No representative of Davco Construction Materials Pty Ltd or any other person has authority to add to, or alter in any way, any MSDS or the information supplied thereon. Any alterations render this MSDS invalid. The information contained herein is believed by Davco Construction Materials Pty Ltd and SSC Pty Ltd to be accurate at the issue date shown and in accordance with information available to us. Persons dealing with the products referred to in this MSDS do so at their own risk since their actions are beyond our control. Davco Construction Materials Pty Ltd and SSC Pty Ltd accepts no liability whatsoever for damage or injury arising from the use of the information contained in this document