



RANDOM MAT

DESCRIPTION

Random Mat is composed of chopped glass strands bonded in mat form with an emulsion binder. It is a thin porous, well-bonded mat, which maintains its integrity during the impregnation process and provides a uniform wet-through rate.

USES

- Random Mat is designed as a reinforcement medium for Davco waterproofing membranes, such as Dampflex and Duraflex
- Major mat characteristics are: good drapability, rapid wet-through and wet-out, and good mechanical properties.
- It is available in 1m wide lengths for reinforcing large areas, and in smaller bands of 125mm and 200mm for junction reinforcing.

SURFACE PREPARATION

Information regarding surface preparation should be obtained from the individual Davco waterproofing membrane, which the random mat is going to be used with.

APPLICATION

Information regarding application methods should be obtained from the individual Davco waterproofing membrane, which the random mat is going to be used with.

COVERAGE

Information regarding coverage data should be obtained from the individual Davco waterproofing membrane, which the random mat is going to be used with.

PACKAGING

Random Mat comes in the following roll sizes:

- 100m² – 1m wide x 100m long
- 12.5m² – 125mm wide x 100m long
- 20m² – 200mm wide x 100m long

PRECAUTIONS

- Unless otherwise specified, it is recommended to store Random Mat in a cool, dry area.
- Temperature should not exceed 35°C and the relative humidity should be kept below 75%.
- Random Mat product must remain in packaging material until just prior to its use.

SHELF LIFE

When stored in a cool, dry area at temperatures less than 35°C and humidity at below 75%, Random Mat can be stored for extended periods of time.

TECHNICAL DATA

Properties:

Appearance: White Mat

Mat Type: Chopped Strand Mat

Dry Weight: 225g/m²

Binder Type: Emulsion

DISCLAIMER

The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. All workmanship must be carried out in accordance with AS 3740:2004.

The information contained herein is to the best of our knowledge true and accurate. No warranty is implied or given as to its completeness or accuracy in describing the performance or suitability of the product for a particular application. Users are asked to check that the literature in their possession is the latest issue.

PAREX DAVCO

ParexDavco (Australia) Pty Limited

ABN 28 093 876 558

67 Elizabeth Street Wetherill Park NSW 2164 Australia

Telephone: 61 2 9616 3000 Facsimile: 61 2 9725 5551

Toll Free Technical Advice Line: 1 800 653 347

Email: technical@parexdavco.com.au Website: www.parexdavco.com.au

