



SANITIZED® COLORGROUT

DESCRIPTION

Davco Sanitized® Colorgrout is a cementitious grout designed for use with most types of ceramic tiles and natural stone applications. The grout also contains a biocide, which provides it with a resistance to a broad spectrum of moulds and bacteria.

Sanitized® Colorgrout is classified as a CG2 grout in accordance with AS4992.1

USES

- Davco Sanitized® Colorgrout can be used in grout joints that are 1 - 6mm wide.
- Davco Sanitized® Colorgrout can be used on internal or external wall and floor grouting applications.
- Davco Sanitized® Colorgrout can also be used in swimming pools and wet areas.

SURFACE PREPARATION

- Before commencing grouting, ensure the tile adhesive has set firmly. This usually requires 24 hours with the majority of tile adhesives.
- Remove any spacer lugs, rake-out any excess adhesive and any loose or foreign material from the grout joints.
- In general, ensure the grout joints are clean and dry.

MIXING

- The mixing ratio is 15kg powder to 3 - 3.4 litres of water (this equals 200 - 225mL per kg)
- Add clean water to a bucket, then slowly add the Sanitized® Colorgrout grout powder to the water. Stir the mix until a lump-free consistency is achieved.
- Allow the mix to stand for 5 minutes, re-stir then use the grout.
- When grouting swimming pools or over timber floors and substrates where movement is expected or for superior performance in general applications, use Davco 4 in 1 Grout Additive instead of water.

APPLICATION

- Prior to grouting it is advisable to lightly dampen the grout joints, particularly with porous tiles or in warmer conditions. If the tiles are particularly porous it is advisable to prime the joints with Davco 4 in 1 Grout Additive after dampening to seal the edge of the tile.
- Using a rubber float or squeegee work the grout into the joints in a diagonal motion making sure that the grout does not just sit on top of the joint i.e. the grout does not bridge the joint.
- Remove excess grout from the surface of the tiles with the rubber float or squeegee using a diagonal motion.
- Use a damp sponge to clean up the remainder of the grout. Regularly rinsing the sponge out to assist in cleaning.
- Finally remove any excess moisture from the grout joints, to avoid discolouration or colour variation problems.
- Allow the grout to cure for 24 hours before cleaning the grout haze with a soft dry cloth. Hard to remove haze can be cleaned with Davco Sanitized® Tile & Grout Cleaner.

PRECAUTIONS

- Do not apply Sanitized® Colorgrout in temperatures above 35°C or below 5°C.
- Sanitized® Colorgrout is not suitable for use in harsh and demanding environments or where there are hygienic requirements i.e. commercial kitchens, public toilets, food processing plants etc. Use Davco Epoxy Grout for these types of installations.
- Cleaning or discolouration problems can occur with either textured, porous or natural stone tiles.
- Sanitized® Colorgrout contains sand and scratching may occur with polished or soft glazed tiles.
- Do not apply Sanitized® Colorgrout in movement joints, use Davco Sanitized® Colorcaulk or Davsil.



SANITIZED® COLORGROUT

- Do not apply neat or strong acids on Sanitized® Colorgrouts.
- For other uses or the use of Sanitized® Colorgrout in situations not mentioned in these instructions, contact your ParexDavco (Australia) Pty Ltd state office.
- Being cement based, Sanitized® Colorgrout is alkali in nature, which can cause dermatitis. Thus when using Sanitized® Colorgrout it is recommended that applicators must wear PVC or similar gloves and safety goggles.
- To help reduce the likelihood of efflorescence formation (white salts), use the minimum amount of wash water and do not exceed the recommended volume of mixing water.
- For a full MSDS on this product, contact your ParexDavco (Australia) Pty Ltd state office.
- All products are guaranteed when installed in accordance with the relevant Australian Standard, the current technical datasheets, specification and instructions for use. This guarantee does not cover issues beyond the control of the manufacturer such as efflorescence, shade variations, variable application techniques and extreme environmental conditions.

COVERAGE

The coverage of the grout will vary depending upon the texture, size and thickness of the tile and the width of the grout joint.

Use the table below as a general guide:

Tile Size (mm)	Quantity of Grout Required kg/m ²			
	Joint Width (mm)			
	1.5	3	6	10
50 x 50 x 6	0.8	1.6	--	--
100 x 100 x 6	0.4	0.8	1.6	--
150 x 150 x 6	0.3	0.6	1.2	--
200 x 100 x 6	0.3	0.6	1.2	--
300 x 300 x 10	0.3	0.5	1.0	--

CLEAN UP

Tools and other equipment can be cleaned up with water while grout is still wet.

PACKAGING

Sanitized® Colorgrout is available in 1.5kg, 5kg & 15kg bags.

SHELF LIFE

Sanitized® Colorgrout has a shelf life of up to 12 months in unopened bags stored in a cool, dry elevated place.

TECHNICAL DATA

Properties:	
Appearance	Various coloured powders
Bulk Density	~ 1.4 kg/litre
Pot Life at 20°C	40 minutes
Curing Time at 20°C	24 hours

DISCLAIMER

The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. All workmanship must be carried out in accordance with AS 3958.1 - 2007.

The information contained herein is to the best of our knowledge true and accurate. No warranty is implied or given as to its completeness or accuracy in describing the performance or suitability of the product for a particular application. Users are asked to check that the literature in their possession is the latest issue.

PAREXDAVCO

ParexDavco (Australia) Pty Limited

ABN 28 093 876 558

67 Elizabeth Street Wetherill Park NSW 2164 Australia

Telephone: 61 2 9616 3000 Facsimile: 61 2 9725 5551

Toll Free Technical Advice Line: 1 800 653 347

Email: technical@parexdavco.com.au Website: www.parexdavco.com.au

